



Model / Series	FARM and FOREST					
Code	47.V.PF	47.388.PD	47.388.PD.K	45.V.PF	45.388.PD	45.388.PD.K
TECHNICAL DATA						
Power supply	PTO 540 RPM	EL 400 V 5,5 kW	EL 400 V + PTO	PTO 540 RPM	EL 400 V 5,5 kW	EL 400 V + PTO
Power Ton	22	20	20	30	30	30
Max cutting diameter cm	100	100	100	130	130	130
Max vertical cutting length cm	124	124	124	124	124	124
Max cutter stroke cm	120	120	120	120	120	120
Hydraulic oil lt.	38	38	38	85	85	85
Pump (PS) (PD) lt. min.	PS x lt. 32,5	PD x lt. 52,5	PD 52,5 + PS 32,5	PS x lt. 53,5	PD x lt. 52,5	PD 52,5 + PS 53,5
Speed and Power * Automatic **	YES **	YES **	YES **	YES **	YES **	YES **
CUTTING SPEED						
1 st cutting speed cm/sec	19	27	27 – 19	20	19	19 – 20
2 nd cutting speed cm/sec	8,5	12	12 – 8,5	9,5	8,5	8,5 – 9,5
Return speed cm/sec	15	22	22 – 15	17,5	16	16 – 17,5
CONTROLS AVAILABLE						
Standard	YES	YES	YES	YES	YES	YES
System-LEADER						
STOPandGO						
TRANSPORT DIMENSIONS and WEIGHT						
Dimensions cm	85x125x230	85x125x230	85x125x230	85x125x230	85x125x230	85x125x230
Weight kg.	550	510	590	610	570	660