













MODEL	MIGNON ECO			MIGNON PROF				
Splitting force	9 ton			11 ton				
Adjustable cutter stroke	50 cm			50 cm				
Min Max. splitting diameter	5 - 50 cm			5 - 60 cm				
Lateral log support extensions (EN 609-1:2017)								
Fall arrest guards (EN 609-1:2017)				•				
Hydraulic oil tank	8.7	'5 lt	9 lt	9 lt				
Controls as standard (Exclusive THOR system)	LEADER			LEADER				
ITEM No.	23.100	23.101	23.102	23.110	23.111	23.112	23.113	23.115
Power supply <b>EL</b> = electric, <b>HVP</b> = tractor, <b>VS</b> = petrol	<b>EL</b> 230 Volt	<b>EL</b> 400 Volt	<b>VS</b> 3200 rpm	<b>EL</b> 230 Volt	<b>EL</b> 400 Volt	<b>VS</b> 3200 rpm	<b>HVP</b> 540 rpm	<b>Kombi</b> EL 400V+HVP
Power required (HP / kW)	3/2.2	4/3	7/5	3/2.2	5.5 / 4	9/6.7	17 / 12.5	5.5 / 4 - 17 / 12.5
Working pressure (bar)  DP = double pump	250	250	250	240/DP	240	230	240	250
1 <sup>st</sup> cutting speed (cm/sec)	4	5.3	4.8	7.9	7.2	4.7	6	7.2 - 10
2 <sup>nd</sup> cutting speed (cm/sec)				1.4				
Return speed (cm/sec)	25	36	32	8.6	16	12.5	16	16 - 16
Full wheels (Ø mm)	300 ■	300 ■	300 ■	300 ■	300 ■	*	200 ■	200 ■
Pneumatic wheels (Ø mm)	*	*	*	*	*	400 ■	0	
Working dimensions $(W \times L / H = 156 \text{ cm})$	125 x 80	125 x 80	125 x 90	125 x 80	125 x 80	125 x 100	125 x 75	125 x 86
Weight (kg)	153	153	160	158	158	181	155	179
Price								

OPTIONAL ACCESSORIES				
Description	Lifting hook	60° cutter	Pneumatic wheels	Side hoist
Item No.	845.201	800.113.K	810.025.K	810.039.K
Price				



## Powerful, safe and persistent! A choice of quality and prestige.








## Shipping dimensions (overall dimensions in cm) // Pallet Weight











**™IGNON** 



