



## TANDEM

MODEL	TANDEM					
Max. cutting diameter	Ø 30 cm					
Widia sawblade hole 30 mm dia. <u>included</u>	Ø 750 mm					
Blade revs (rpm)	1400					
Conveyor belt	4 m			5 m		
Width x Length	0.25 x 3.70 m			0.25 x 4.70 m		
Max. discharge height at 45°		3.10 m ~				
ITEM No.	K76.101	K76.103	K76.104	K <b>76</b> .111		
Power supply saw benches and belt: <b>V.PF</b> = tractor, <b>EL</b> = electric (S6), <b>Kombi</b>	<b>V.PF</b> 540 rpm	EL 400 Volt	Kombi (EL + V.PF)	<b>V.PF</b> 540 rpm		
Power required (HP / kW)	25 / 18	12/9	7.5 / 5.5 - 25 / 18	25 / 18		
Blade stopping brake	•	-	•			
3-point connector 1 <sup>st</sup> - 2 <sup>nd</sup> cat.	•	-	•	•		
Cut adjuster and discharge conveyor for conveyor belt	•	•	•	•		
Side foldable logs feed	•	-	•	•		
Transport height with closed belt (m)	2.50	2.50	2.50	3.50		
Working dimensions (W x L x H cm)	170 x 450 x 250 (with belt at 45° / 4 m)					
Weight (kg)	500	510	550	530		
Price						

OPTIONAL ACCESSORIES				
Description	Cardan shaft with safety bolt	Speed adjuster for belt	Extension kit for <b>5 m</b> belt not assembled (Tandem: 4 m)	
Item No.	600.125	853.033.K	853.020.K	
Tractor (V.PF)	*	*	*	THE
Electric		*	*	
Price				Transport position



#### Saw bench with conveyor belt for industrial and agricultural use!






### SAW BENCHES

#### Shipping dimensions (overall dimensions in cm) // Pallet Weight

KATANA »700










**VS** version




Pallet Weight: 25 kg

# KATANA »750




V.PF / EL / KOMBI versions






**VS** version





Pallet Weight: 25 kg







\*<u>V.PF version - Cod. 76.111</u>:

- Saw benches height = 215 cm
- Belt dimensions = 340 x 70 x 70 cm
- \*\*<u>EL version Cod. 76.103</u>:
  - Packaging depth = 128 cm