

## Their power has no rivals!

- The frame has been designed in minute detail. The cutter and the guides are designed for the hardest and most demanding uses.
- All the hydraulic, mechanical and electrical components are of top quality, exclusively produced in the EU.
- They are powerful and safe thanks to the "System-LEADER" controls on all versions.
  With the "System-LEADER" controls you can carry out the cutter approach stroke and center the logs while the cutter is in motion with both hands free by using the pedal! Once the log is centered and blocked in the desired position the two control levers are used to split the log.
- The range icludes electrical versions (230 Volt single-phase or 400 Volt three-phase), petrol engine VS version, HVP for tractor and the KOMBI versions.







Model	Lider	Lider	Lider
Cutting force	9 Ton	9 Ton	9 Ton
Power supply <i>EL</i> = electric motor, <i>VS</i> = petrol engine	EL 230 Volt	<b>EL</b> 400 Volt	VS
Performance (HP / kW)	3 / 2,2	4 / 3	7 / 5
Max. cutting height (cm)	54-67-105	54-67-105	54-67-105
Adjustable cutter stroke (cm)	50	50	50
Max cutting diameter (cm)	50	50	50
Working pressure (bar) PD = double pump	250 /PD	240	240
1 <sup>st</sup> cutting speed (cm/sec)	10	5,3	4
2 <sup>nd</sup> cutting speed (cm/sec)	1,8		
Return speed (cm/sec)	12,4	36	27
Hydraulic oil tank capacity (lt)	8,75	8,75	8,75
Weight (kg)	140	140	150
Shipment dimensions (AxBxH cm)	60x80x130	60x80x130	80x120x130
Rear control cover	•	٠	•
Wheel size (mm dia.) <i>full</i>	300	300	300
"System-LEADER" control with pedal included	•	٠	•
List price excl. VAT (€)			
Net price excl. VAT (€)			
🗘 = delivery time: 4 weeks			
Code	73.223.PD	73.384.90	73.VS.55

 $\Box = NO \bullet = YES$ 

OPTIONAL ACCESSORIES				R
Description	60° cutter	Cross cutter	Side extension for log support	400 dia. pneumatic
for logs w		raight filaments	before and after splitting	wheels kit
Code	800.087.K	800.086.K	800.076.K	810.025.K