



Model: **PORTA-TUTTO**

**TROLLEY-EQUIPPED TELESCOPIC TRANSPORTER**

*They are useful and indispensable for many applications!*

- They are very compact and sturdy, they take up little transport space.
- These models are available with (HV) hydraulic connections, or with electrical 230 or 400 Volt motor.
- Sturdy frames in pressed, high-resistance metal sheet, 2 mm and 6 mm width.
- Powder painted and coated with zinc, durable even outdoors.
- Telescopic extraction by manual winch.



400 dia. full wheels as standard.  
**OPTIONAL: Code 835.029.K**  
 Pneumatic wheels 500 dia.



Model	Porta-Tutto 230 V	Porta-Tutto 400 V	Porta-Tutto HV
Power supply <i>EL</i> = electric motor, <i>HV</i> = hydraulic connections	EL 230 Volt 1 HP	EL 400 Volt 1 HP	Hydraulic connections CC.100
Length of the belt (completely open) (m)	4.40 ~	4.40 ~	4.40 ~
Belt width (cm)	25	25	25
Vulcanized PVC blades, 6 cm. h, (n° of blades)	13	13	13
Double-ply PVC mat with metal coupling	●	●	●
Upper tow mat	●	●	●
Max. load height (45° = m)	3.10 ~	3.10 ~	3.10 ~
Manual winch for extraction	●	●	●
Manual screw for load height regulation	●	●	●
Wheels for short movements (dia. mm) <i>full</i>	2 x 400	2 x 400	2 x 400
Draw bar for short movements	●	●	●
Anti-return screen for greater operator safety	●	●	●
Speed adjuster (hydraulic)	□	□	optional 853.033.K
Weight (kg)	234	234	230
<b>List price excl. VAT (€)</b>			
<b>Net price excl. VAT (€)</b>			
★ = delivery time: 4 weeks	★	★	★
<b>Code</b>	<b>TTC.025.5.231</b>	<b>TTC.025.5.381</b>	<b>TTC.025.5.HV</b>

□ = NO ● = YES

OPTIONAL ACCESSORIES	SPARE PARTS				
Description	5 mt mat with blades	Anti-return screen	Mat for hopper	pneumatic wheels 500 dia.	Speed adjuster for HV belt
Code	200.165	200.138	200.139	835.029.K	853.033.K